NAME	LOCATION	SPECIFIER

HOUSING

AT402 - G - ☐☐☐

FINISH

- ☐☐☐ Silver *(Standard- leave blank)*
- BRZ Dark Bronze

LIGHT ENGINE

☐☐24 - ☐☐ - ☐☐☐

LIGHT ENGINE	COLOR CODE	MODEL TYPE
95 9524	22 2150K	LE Light Engine
49 4924	24 2350K	FR Frangible Rigid
65 6524	26 2550K*	
	27 2650K	
	30 2950K	
	35 3450K	
	40 3950K	
	55 5500K†	
	A Amber	
	B Blue	
	R Red	
	G Green	

*2550K ONLY AVAILABLE 3000, 4000 & 8000 SERIES LE

† 5500K ONLY AVAILABLE 9000-FR

LEADS

POWER LEADS	JUMPER W/ DISCONNECT PLUGS	HARD WIRED JUMPERS
AC-A24 White 24"	AC-BP4 White	AC-C4 White
ACB-A24 Black 24"	ACB-BPB4 Black	ACB-C4 Black
AC-A Custom	AC-BP Custom	AC-C Custom

REFERENCE LEADS & PLUGS CONFIGURATION TYPES PAGE

DRIVER

DC
MLV DIMMING

- ☐ D50-DC
- ☐ D100-DC
- ☐ D300-DC3

- ☐ 120 VAC
- ☐ 240 VAC
- ☐ 277 VAC

Z
0-10V DIMMING

- ☐ D100-Z2
- ☐ D100-Z

X
DMX, 1 CHANNEL

- ☐ D100-X1

DMX CONTROLLER

- ☐ AX5-1
- ☐ DTM

M
NON DIMMING

- ☐ D12-M
- ☐ D20-M
- ☐ D40-M
- ☐ D100-M

A
LUTRON

- ☐ D40-A
  Hi-lume 1% 2-wire UL-Recognized Constant Voltage, 40W
- ☐ D40-A-R
  Hi-lume 1% 2-wire UL-Listed Constant Voltage, 40W
- ☐ D40-A-L3D
  Hi-lume 1% EcoSystem/3-Wire UL-Recognized Constant Voltage
- ☐ D40-A-L3D-R
  Hi-lume 1% EcoSystem/3-Wire UL-Listed Constant Voltage, 40W
- ☐ D100-A
  Hi-lume Premier 0.1% UL-Listed Constant Voltage, 96W

Required Fixture Lengths

Please input fixture lengths/ quantity & configuration types

ZONE	LENGTH	QUANTITY	CONFIGURATION TYPE

Notes

Refer to Light Engine Data Sheets for Light Engine Increments.
Track is cut to exact length (1/8" tolerance)
Allow tolerance for wiring/ plugs
Fixtures up to Class 2 max. length

Custom Lengths

Fully assembled up to ≤ 8 ft. (96 in).
Fixtures > 8 ft. (96 in) require assembly at the job site.

SIGNATURE (Required if Final Lengths)

- ☐ Final Order Lengths*
- ☐ Budgetary only, requires field verification

Component of a complete system including: Aion LED A-Track Light Engine, Aion LED A-Track housing with diffuser lens, & Aion LED driver (power supply). Dimmer not included. Approved dimmers, controls, power supplies, cable, & other components only. Contact Aion LED for questions regarding compatibility. Electrician installed. Strictly adhere to NEC & local building code. Limited 5-year warranty against manufacturing defects only, does not cover labor; voided by: inadequate ventilation, field modifications, installation by unqualified personnel, unapproved controls, drivers, cabling, other devices, not following installation guidelines & protocol, general negligence. Installer assumes all liability with regard to property & safety. This product is UL listed. See separate "Aion LED Warranty Terms" & additional instructional materials for more information. Authorized installers only. Systems tested prior to shipping.

© 2017 Aion LED. All Rights Reserved