

Low-Voltage Class 2/3 Power Cable by Aion LED White/ Static System UL Approved UV Rated Indoor/ Outdoor

Fixture Power Lead

FIXTURE POWER LEAD	WHITE JACKET	BLACK JACKET	
12" power lead	AC-A12	ACB-A12	
24" power lead	AC-A24	ACB-A24	
48" power lead	AC-A48	ACB-A48	

Hard Wire Jumper- Recommended with WR Type & LE Applications Only

HARD WIRED JUMPER 4" Hard Wired Jumper 12" Hard Wired Jumper 24" Hard Wired Jumper	WHITE JACKET AC-C4 AC-C12 AC-C24	BLACK JACKET ACB-C4 ACB-C12 ACB-C24	

Bi Pin Plugs- Recommended with all AT Series Housings & Fixtures

Bi PIN JUMPER w/ disconnect	WHITE JACKET	BLACK JACKET		70
4" Jumper with Disconnect	AC-BP4	AC-BPB4		
12" Jumper with Disconnect	AC-BP12	AC-BPB12		
24" Jumper with Disconnect	AC-BP24	AC-BPB24		
48" Jumper with Disconnect	AC-BP48	AC-BPB48	8.08mm 0 10.59mm	27.69mm

Patch Cord- Optional, to Extend Length

24" M to F Extension Cord BP-2FM24 BPB-2FM24 48" M to F Extension Cord BP-2FM48 BPB-2FM48 96" M to F Extension Cord BP-2FM96 BPB-2FM96
96" M to F Extension Cord BP-2FM96 BPB-2FM96

Black standard for dark bronze housings White standard for silver housings





A-TRACK | CONFIGURATION TYPES

Unless Otherwise Noted, Leads are 24" and Plugs are 4". Other Lengths Available **CONFIGURATION 1** Power Lead to Fixture Default, Unless Otherwise Noted **CONFIGURATION 2** Power Lead to Fixture with End Lead **CONFIGURATION 3** Power Lead to Fixture with End Plug **CONFIGURATION 4** =------Power Plug to Fixture with End Plug **CONFIGURATION 5** ______ Power Plug to Fixture **CONFIGURATION 6 Not Compatible with Track** Power Lead to Fixture with Jumper to Next Fixture **CONFIGURATION 7 Not Compatible with Track** Jumper to Fixture with Jumper to Next Fixture **CONFIGURATION 8 Not Compatible with Track** 0000000 ______ Jumper to Fixture A-TRACK FIXTURES Pre-assembled: ≤ 8 ft (96 in) Assembly Required: > 8 ft (96 in)