



NAME

TYPE

SPECIFIER

HOUSING	ST850 	 LENS <input type="checkbox"/> F Frosted <input type="checkbox"/> C Clear <input type="checkbox"/> P Prismatic	 FINISH <input type="checkbox"/> B L K Black <input type="checkbox"/> W H T White	Required Fixture Lengths Please input fixture lengths/ quantity & configuration types																																																												
	ST850-C CORNER 	 LENS <input type="checkbox"/> F Frosted <input type="checkbox"/> C Clear <input type="checkbox"/> P Prismatic	 FINISH <input type="checkbox"/> B L K Black <input type="checkbox"/> W H T White																																																													
LIGHT ENGINE	 LIGHT ENGINE	 COLOR CODE	 MODEL TYPE	<table border="1"> <thead> <tr> <th>ZONE</th> <th>FIXTURE LENGTH</th> <th>SUSPENSION DISTANCE</th> <th>QUANTITY</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>	ZONE	FIXTURE LENGTH	SUSPENSION DISTANCE	QUANTITY																																																								
	ZONE	FIXTURE LENGTH	SUSPENSION DISTANCE		QUANTITY																																																											
<table border="1"> <tr> <td><input type="checkbox"/> 9 5 9524</td> <td><input type="checkbox"/> 8 9 8924</td> <td><input type="checkbox"/> 2 2 2150K</td> <td><input type="checkbox"/> A Amber</td> <td><input type="checkbox"/> L E Light Engine</td> </tr> <tr> <td><input type="checkbox"/> 6 5 6524</td> <td><input type="checkbox"/> 4 9 4924</td> <td><input type="checkbox"/> 2 4 2350K</td> <td><input type="checkbox"/> B Blue</td> <td><input type="checkbox"/> F R Frangible Rigid</td> </tr> <tr> <td><input type="checkbox"/> 3 9 3924</td> <td></td> <td><input type="checkbox"/> 2 6 2550K*</td> <td><input type="checkbox"/> R Red</td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> 2 7 2650K</td> <td><input type="checkbox"/> G Green</td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> 3 0 2950K</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> 5 5 3450K</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> 4 0 3950K</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> 5500K†</td> <td></td> <td></td> </tr> </table>	<input type="checkbox"/> 9 5 9524	<input type="checkbox"/> 8 9 8924	<input type="checkbox"/> 2 2 2150K	<input type="checkbox"/> A Amber	<input type="checkbox"/> L E Light Engine	<input type="checkbox"/> 6 5 6524	<input type="checkbox"/> 4 9 4924	<input type="checkbox"/> 2 4 2350K	<input type="checkbox"/> B Blue	<input type="checkbox"/> F R Frangible Rigid	<input type="checkbox"/> 3 9 3924		<input type="checkbox"/> 2 6 2550K*	<input type="checkbox"/> R Red				<input type="checkbox"/> 2 7 2650K	<input type="checkbox"/> G Green				<input type="checkbox"/> 3 0 2950K					<input type="checkbox"/> 5 5 3450K					<input type="checkbox"/> 4 0 3950K					<input type="checkbox"/> 5500K†			<small>*2550K ONLY AVAILABLE 3000, 4000 & 8000 SERIES LE</small> <small>†5500K ONLY AVAILABLE 9000-FR</small>																							
<input type="checkbox"/> 9 5 9524	<input type="checkbox"/> 8 9 8924	<input type="checkbox"/> 2 2 2150K	<input type="checkbox"/> A Amber	<input type="checkbox"/> L E Light Engine																																																												
<input type="checkbox"/> 6 5 6524	<input type="checkbox"/> 4 9 4924	<input type="checkbox"/> 2 4 2350K	<input type="checkbox"/> B Blue	<input type="checkbox"/> F R Frangible Rigid																																																												
<input type="checkbox"/> 3 9 3924		<input type="checkbox"/> 2 6 2550K*	<input type="checkbox"/> R Red																																																													
		<input type="checkbox"/> 2 7 2650K	<input type="checkbox"/> G Green																																																													
		<input type="checkbox"/> 3 0 2950K																																																														
		<input type="checkbox"/> 5 5 3450K																																																														
		<input type="checkbox"/> 4 0 3950K																																																														
		<input type="checkbox"/> 5500K†																																																														
LEADS	POWER LEADS <input type="checkbox"/> A C A 9 6 White 96" <input type="checkbox"/> A C B A 9 6 Black 96" <input type="checkbox"/> A C A Custom	TOTAL SUSPENSION POINTS <input type="checkbox"/> S K 2 2 <input type="checkbox"/> S K 3 3 <input type="checkbox"/> S K 4 4		Notes Refer to Light Engine Data Sheets for Light Engine Increments. Track is cut to exact length (1/8" tolerance) Allow tolerance for wiring/ plugs Fixtures up to Class 2 max. length																																																												
	<table border="1"> <thead> <tr> <th colspan="2">DC MLV DIMMING</th> <th>Z 0-10V DIMMING</th> <th>X DMX, 1 CHANNEL</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> D50-DC</td> <td><input type="checkbox"/> 120 VAC</td> <td><input type="checkbox"/> D100-Z2</td> <td><input type="checkbox"/> D100-X1</td> </tr> <tr> <td><input type="checkbox"/> D100-DC</td> <td><input type="checkbox"/> 240 VAC</td> <td><input type="checkbox"/> D100-Z</td> <td><input type="checkbox"/> DMX CONTROLLER</td> </tr> <tr> <td><input type="checkbox"/> D300-DC3</td> <td><input type="checkbox"/> 277 VAC</td> <td></td> <td><input type="checkbox"/> AX5-1 <input type="checkbox"/> DTM</td> </tr> </tbody> </table>	DC MLV DIMMING			Z 0-10V DIMMING	X DMX, 1 CHANNEL	<input type="checkbox"/> D50-DC	<input type="checkbox"/> 120 VAC	<input type="checkbox"/> D100-Z2	<input type="checkbox"/> D100-X1	<input type="checkbox"/> D100-DC	<input type="checkbox"/> 240 VAC	<input type="checkbox"/> D100-Z	<input type="checkbox"/> DMX CONTROLLER	<input type="checkbox"/> D300-DC3	<input type="checkbox"/> 277 VAC		<input type="checkbox"/> AX5-1 <input type="checkbox"/> DTM																																														
DC MLV DIMMING		Z 0-10V DIMMING	X DMX, 1 CHANNEL																																																													
<input type="checkbox"/> D50-DC	<input type="checkbox"/> 120 VAC	<input type="checkbox"/> D100-Z2	<input type="checkbox"/> D100-X1																																																													
<input type="checkbox"/> D100-DC	<input type="checkbox"/> 240 VAC	<input type="checkbox"/> D100-Z	<input type="checkbox"/> DMX CONTROLLER																																																													
<input type="checkbox"/> D300-DC3	<input type="checkbox"/> 277 VAC		<input type="checkbox"/> AX5-1 <input type="checkbox"/> DTM																																																													
DRIVER	<table border="1"> <thead> <tr> <th>M NON DIMMING</th> <th>A LUTRON</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> D12-M</td> <td><input type="checkbox"/> D40-A Hi-lume 1% 2-wire UL-Recognized Constant Voltage, 40W</td> </tr> <tr> <td><input type="checkbox"/> D20-M</td> <td><input type="checkbox"/> D40-A-R Hi-lume 1% 2-wire UL-Listed Constant Voltage, 40W</td> </tr> <tr> <td><input type="checkbox"/> D40-M</td> <td><input type="checkbox"/> D40-A-L3D Hi-lume 1% EcoSystem/3-Wire UL-Recognized Constant Voltage</td> </tr> <tr> <td><input type="checkbox"/> D100-M</td> <td><input type="checkbox"/> D40-A-L3D-R Hi-lume 1% EcoSystem/3-Wire UL-Listed Constant Voltage, 40W</td> </tr> <tr> <td></td> <td><input type="checkbox"/> D100-A Hi-lume Premier 0.1% UL-Listed Constant Voltage, 96W</td> </tr> </tbody> </table>	M NON DIMMING	A LUTRON	<input type="checkbox"/> D12-M	<input type="checkbox"/> D40-A Hi-lume 1% 2-wire UL-Recognized Constant Voltage, 40W	<input type="checkbox"/> D20-M	<input type="checkbox"/> D40-A-R Hi-lume 1% 2-wire UL-Listed Constant Voltage, 40W	<input type="checkbox"/> D40-M	<input type="checkbox"/> D40-A-L3D Hi-lume 1% EcoSystem/3-Wire UL-Recognized Constant Voltage	<input type="checkbox"/> D100-M	<input type="checkbox"/> D40-A-L3D-R Hi-lume 1% EcoSystem/3-Wire UL-Listed Constant Voltage, 40W		<input type="checkbox"/> D100-A Hi-lume Premier 0.1% UL-Listed Constant Voltage, 96W		Custom Lengths Pre-assembled: ≤ 8 ft (96 in) per section																																																	
	M NON DIMMING	A LUTRON																																																														
<input type="checkbox"/> D12-M	<input type="checkbox"/> D40-A Hi-lume 1% 2-wire UL-Recognized Constant Voltage, 40W																																																															
<input type="checkbox"/> D20-M	<input type="checkbox"/> D40-A-R Hi-lume 1% 2-wire UL-Listed Constant Voltage, 40W																																																															
<input type="checkbox"/> D40-M	<input type="checkbox"/> D40-A-L3D Hi-lume 1% EcoSystem/3-Wire UL-Recognized Constant Voltage																																																															
<input type="checkbox"/> D100-M	<input type="checkbox"/> D40-A-L3D-R Hi-lume 1% EcoSystem/3-Wire UL-Listed Constant Voltage, 40W																																																															
	<input type="checkbox"/> D100-A Hi-lume Premier 0.1% UL-Listed Constant Voltage, 96W																																																															
			SIGNATURE (Required if Final Lengths) <input type="checkbox"/> Final Order Lengths* <input type="checkbox"/> Budgetary only, requires field verification																																																													

Component of a complete system including: Aion LED A-Track Light Engine, Aion LED A-Track housing with diffuser lens, & Aion LED driver (power supply). Dimmer not included. Approved dimmers, controls, power supplies, cable, & other components only. Contact Aion LED for questions regarding compatibility. Electrician installed. Strictly adhere to NEC & local building code. Limited 5-year warranty against manufacturing defects only, does not cover labor; voided by inadequate ventilation, field modifications, installation by unqualified personnel, unapproved controls, drivers, cabling, other devices, not following installation guidelines & protocol, general negligence. Installer assumes all liability with regard to property & safety. This product is UL listed. See separate "Aion LED Warranty Terms" & additional instructional materials for more information. Authorized installers only. Systems tested prior to shipping.