

NAME			LOCATION		SPECIFIER			
HOUSING	AT AT SERIES HOUSING		F Frosted P Prismatic C Clear G Grazer (AT402 only)	FINISH Silver (Standard- leave blank) BRZ Dark Bronze	Required Fixture Lengths Please input fixture lengths/ quantity & configuration types Standard Lengths Light Engines are cut to minimum increments Track measurements are rounded down and cut to the inch. 1" tolerance Precision Lengths Light Engines are cut to minimum increments Track measurements are rounded down and cut to the inch. 1" tolerance Description Light Engines are cut to minimum increments Track is cut to a fraction of an inch. 1/8" tolerance ZONE LENGTH QUANTITY CONFIGURATION			
MOUNTING	Standard Mounting Clips ((Standard)			LENGTH	QUANTITY	TYPE
			T40-MC-P3 AT80-M	C-P1 AT80-MC-P3 s A-Track, 1" 800 Series A-Track, 3"				
LIGHT ENGINE	24			-				
	LIGHT ENGINE		COLOR CODE	MODEL TYPE				
	9 <u>5</u> 9524 1 <u>5</u> 1524	898924 494924 393924	2 2 2150K Amber 2 4 2350K B Blue 2 6 2550K' R Red 2 7 2650K G Green 3 0 2950K *2550K ONLY 3 5 3450K 400 a 8000 4 0 3950K † 5500K ONLY 5 5 5500K ⁺ † 5500K ONLY	LE Light Engine FR Frangible Rigid 9524 ONLY				
	POWER LEADS		JUMPER W/ DISCONNECT PLUGS	HARD WIRED JUMPERS				
LEADS	AC A2 ACBA2 AC A	4 Black 24" Custom	AC-BP4 White ACB-BP4 Black AC-BP Custom	AC-C4 White ACB-C4 Black AC-C Custom	Notes	isht Enging	Data Shaai	
DRIVER	DC		Z	X	Refer to Light Engine Data Sheets for Light Engine Increments.		S IOI LIGIT	
	D50-DC D100-DC D300-DC3	120 VAC 240 VAC 277 VAC	0-10V	DMX, 1 CHANNEL D100-X1 DMX CONTROLLER AX5-1 DTM	Fixtures u Fully asse	up to Class embled up t > 8 ft. (96 in	viring/ plugs 2 max. leng to ≤ 8 ft. (96) may require	
	M DM NON 0-10V DIMMING DIMMING MODULE		A LUTRON					
	D12-M DM-Z1 D20-M D40-M D100-M		 D40-A, Hi-lume 1% 2-wire, Constant Voltage, UL- Recognized, 40W D40-A-R, Hi-lume 1% 2-wire, Constant Voltage, UL-Listed, 40W 	 D40-A-L3D, Hi-lume 1% EcoSystem/3-Wire, Constant Voltage, UL-Recognized, 40W D40-A-L3D-R, Hi-lume 1% EcoSystem/3-Wire, Constant Voltage, UL-Listed, 40W D100-A, Hi-lume Premier 0.1%, Constant Voltage, UL-Listed, 96W 	SIGNATURE Final Order Lengths (Requires Signature) Budgetary only, requires field verification			

Components of a complete system include: Aion LED A-Track Light Engine, Aion LED A-Track housing with diffuser lens, & Aion LED driver (power supply). Dimmer not included. Approved dimmers, controls, power supplies, cable, & other components only. Contact Aion LED for questions regarding compatibility. Electrician installed. Strictly adhere to NEC & local building code. Limited 5-year warranty against manufacturing defects only, does not cover labor; voided by: inadequate ventilation, field modifications, installation by unqualified personnel, unapproved controls, drivers, cabling, other devices, not following installation guidelines & protocol, general negligence. Installer assumes all liability with regard to property & safety. This product is UL listed. See separate "Aion LED Warranty Terms" & additional instructional materials for more information. Authorized installers only. Systems tested prior to shipping.

